

11 ABBREVIATIONS AND FORMALITIES

STRUTFAST

Abbreviations

A	Amps (Ampere)
ABS	Acrylonitrile Butadiene Styrene
C/W	Complete With
DEG	Degrees
DED	Dedicated
DPI	Double Pole Isolator
D/P	Distribution Point
EXT	External
EPC	Epoxy Powder Coated
E.G	Electro Galvanized
HOR	Horizontal
H.D.G	Hot Dip Galvanized
INT	Internal
ID	Inside Diameter
M	Metric
OD	Outside Diameter
PG	Pre-Galvanized
POR	Price On Request
PVC	Poly-Vinyl Chloride
SO	Socket Outlet
SSO	Switched Socket Outlet
STD	Standard
SPI	Single Pole Isolator
SD	Space Dock
∅	Diameter Symbol
RAD	Internal Radius in mm

Formalities

1. All prices quoted are per each.
2. Prices for products, materials and finishes not shown are available on request.
3. Prices are Ex-Works, exclude VAT and are subject to change.
4. Strutfast reserves the right to change the design of, or discontinue any of its products.
5. Prices shown are in South African Rands.
6. Prices offered are in accordance with our Standard conditions of Agreement which form part of Strutfast's Credit Application Document
7. E&OE.

Materials and Finish Index

Pre-Galvanised to SABS ISO 3575:1996 - BS EN 10143:1992 (Formerly SABS 934 / BS 2989), normally grade Z275

Hot-Dip Galvanized Mild Steel to BS 1449 Part 1, Hot-dip Galvanized to SABS ISO 1461:1999

Zinc Electroplated Mild Steel 5 to 8 microns with bright passivation to SABS ISO 4042:1999 (BS 7371 Part 1:1991) for threaded articles up to 19mm diameter

Epoxy Powder coating to SABS 1274:1979. Various different powder coating types for indoor, outdoor, industrial, marine and marine industrial applications are available

SS304 - Stainless Steel Grade 304

SS316 - Stainless Steel Grade 316